



NEOFLEX™ PREMIUM GYM TILES (NO PAIN NO GAIN)

SKU: NEOFLEX-PGT-NPNG





PRODUCT
DESCRIPTION

These 15 mm x 1m x 1m rubber tiles are easily installed and are a cost effective choice for a very tough, sound deadening, anti-vibration and comfortable tile surface is preferred. For an indoor setting, you can loose lay them or bond them down using the 4 x Stikibak tabs provided on the back. These tiles are used for the official competition floor of some of Europe's largest CrossFit events like The German Throwdown.

Specs:

| Property | Standard | Result |
|--------------------------|----------------|----------------------------------|
| Thickness | | 15 mm |
| Dimensions | | 1010 mm x 1010 mm |
| Weight | | 15.0 kgs |
| Shore Hardness A | | 60° |
| Resilience | ASTM D 2240 | 40% |
| Tear Strength Top Layer | ASTM D 624 | 1.55 MPa (± 225 psi) |
| Tear Strength Base layer | ASTM D 624 | 0.70 MPa (± 101 psi) |
| Taber Abrasion | ASTM C 504 | 0.66 gr |
| Remaining Indentation | DIN 53960 | 0.05 mm |
| Flammability | EN 13501-1 | Class Cf1-s1 |
| | ASTM E648 | Class I [4.4 kW/m ²] |
| Coefficient of Friction | ASTM D 2047-97 | Dry: 1.03 Wet: 0.97 |

ADDITIONAL
INFORMATION

More Information

Warranty

6 months